



Cold Planers

For Skidsteers and Compact Track Loaders

18, 24", 30" and 40" cutting widths; 0-8" cutting depth

5 inch tooth tip to drum surface decreases drag in the cut

Hydraulic tilt, depth and sideshift of cutting drum

Sauer 2.68 cu in M44 piston motor / 24:1 Fairfield planetary drive hub

Optional 40 gallon ROPS mounted water system

Optional drum widths to fit any job requirement



Applications:

Milling asphalt prior to overlay

Cutting utility trenches

Base material reclamation

Pothole and shoulder repair

Restoring drainage elevation

Removing trip hazards

Model	Min GPM / PSI	Cutting Width	Cutting Depth	# Cutting Teeth	Tilt	Sideshift	Weight
CP18HD	27 / 2,750	18 inches	0-8 inches	46	+/- 15 deg.	26 inches	1,690
CP24HD	30 / 2,750	24 inches	0-8 inches	56	+/- 13 deg.	26 inches	2,120
CP30HD	34 / 3,000	30 inches	0-8 inches	66	+/- 10 deg.	26 inches	2,770
CP40HD	37 / 3,450	40 inches	0-8 inches	76	+/- 8 deg.	26 inches	2,910

RoadHog, Inc. • 877-640-9975 • www.roadhoginc.com • sales@roadhog-inc.com

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

Rev 2/20